

CLAIM AMENDMENTS

Claim Amendment Summary

Claims pending

- Before this Amendment: Claims 1-4, 7, 9-15, 17-20, 24-28, 31, 33 and 35-38.
- After this Amendment: Claims 1-2, 4, 9-15, 17-20, 24-28, 31, 33, and 35-38.

Newly Non-Elected, Canceled, or Withdrawn claims: 3, 5, and 7-8.

Amended claims: 1-2, 4, 9-15, 20, 24-28, 31, 33, and 35-38.

New claims: None.

Claims:

1. (Currently Amended) A method comprising:

receiving a message at a routing node in an overlay network, the message comprising a header and a body, wherein the header comprises information for routing the message;

passing the message to the application level at the routing node to process the message;

generating a routing policy for a sending node based at least in part on ~~content~~ the body of the message, wherein the routing policy comprises instructions for redirecting messages based at least in part on the ~~content~~ body of the message;

returning the routing policy to the sending node;

identifying a final destination address to which to route the message; and

incorporating the routing policy into the body of the message and
forwarding the message to ~~another~~ the final destination node in the overlay network.

2. (Currently Amended) The method of claim 1, further comprising comprising:

modifying ~~[[the]]~~ an address of the header of the message; message to create a modified address;

determining from the message if the sending node does not have routing policy instructions derived from the body of the message after the message is passed to the application level of the routing node; and

generating the routing policy based on the modified address and returning the routing policy to the sending node if it is determined that the sending node does not have routing policy instructions derived from the body of the message.

3. (Canceled)

4. (Currently Amended) The method of claim 1, wherein generating the routing policy is at an application level in the routing node, and wherein a compression policy is applied to the message prior to returning the routing policy to the sending node.

5. – 8. (Canceled)

9. (Currently Amended) The method of ~~claim 7~~ claim 1, further comprising iteratively applying by the node a plurality of routing policies to the message, each of the plurality of routing policies modifying the address in the message, and applying by the node a security policy to the message.

10. (Currently Amended) The method of ~~claim 7~~ claim 1, further comprising receiving the at least one routing policy at a sending node in the overlay network.

11. (Currently Amended) The method of ~~claim 7~~ claim 1, further comprising receiving a plurality of routing policies at a sending node from a plurality of routing nodes in the overlay network.

12. (Currently Amended) The method of ~~claim 7~~ claim 1, wherein identifying at least one routing policy is based at least in part on the address of the header of the message.

13. (Currently Amended) The method of ~~claim 7~~ claim 1, further comprising applying a transport policy to the message after changing the address in the header of the message, wherein the transport policy defines which transportation protocol with which to send the message.

14. (Currently Amended) The method of ~~claim 7~~ claim 1, further comprising comprising:

applying a transport policy to the message only after applying each identified routing policy to the message, wherein the transport policy defines a transportation protocol over which to transport the message, and
applying an encryption policy before issuing the message directly to the final destination node in the overlay network.

15. (Currently Amended)

A system comprising:

a routing node receiving a message in an overlay network, wherein the message comprises a body and a header, wherein the header comprises information for routing the message;

routing table operatively associated with the routing node; and

a message processor at the routing node, the message processor generating a routing policy for a sending node of the message and incorporating the routing policy into the body of the message, wherein the routing policy comprises instructions for redirecting messages based at least in part on content of the body of the message, the message processor generating the routing policy based on entries in the routing table, and the message processor applying a security policy to the message.

16. (Canceled)

17. (Original)

The system of claim 15, wherein the routing node includes a messaging level and an application level, the routing node generating the routing policy at the application level.

18. (Original) The system of claim 15, wherein the routing node includes a messaging level and an application level, the routing node returning the routing policy to the sending node at the messaging level.

19. (Original) The system of claim 15, wherein the routing node includes a messaging level and an application level, the routing node forwarding the message to another node in the overlay network at the messaging level.

20. (Currently Amended)

A system comprising:

at least one routing policy for a message, the message comprising a header and a body, wherein the header comprises information for routing the message, wherein the at least one routing policy is generated by at least one routing node in the an overlay network, wherein the routing policy comprises instructions for redirecting messages;

~~a policy manager to identify the at least one routing policy to the messaging module based at least in part on content of the body of the message;~~
and

a messaging module ~~changing~~ configured to change an address in the header of the message at the a sending node to bypass at least one node in [[an]] the overlay network based on the at least one routing policy so that the message is issued directly to a final destination node in the overlay network, wherein the messaging module is configured to incorporate the routing policy into the body of the message; and

a policy manager configured to identify the at least one routing policy to the messaging module based at least in part on content of the body of the message.

21. – 23. (Canceled)

24. (Currently Amended) The system of claim 20, further comprising a transport policy identifying a transport protocol for the message based on the address in the header of the message, and wherein the messaging module is further configured to determine from the message if the sending node does not have routing policy instructions derived from the body of the message, and wherein the policy manager is configured to return the routing policy to the sending node if it is determined that the sending node does not have routing policy instructions derived from the body of the message.

25. (Currently Amended) A computer program storage medium storing a computer program for executing on a computer system a ~~computer process, the computer process~~ method, the method comprising:

receiving a message at a routing node in an overlay network, wherein the message comprises a body and a header, wherein the header comprises information for routing the message;

passing the message to the application level at the routing node to process the message;

generating a routing policy for a sending node of the message, wherein the routing policy comprises instructions for redirecting messages based at least in part on content of the body of the message, and incorporating the routing policy into the body of the message;

returning the routing policy to the sending node;

identifying a final destination address to which to route the message; and

forwarding the message to ~~another~~ a final destination node in the overlay network.

26. (Currently Amended) The computer program storage medium of claim 25 wherein the ~~computer process~~ method further ~~comprises~~ comprises:

~~identifying an address to route the message; and~~
~~generating the routing policy based on the address; and~~
~~applying a compression policy to the message prior to returning the~~
~~routing policy to the sending node.~~

27. (Currently Amended) The computer program storage medium of claim 25 wherein the ~~computer process further comprises passing the message to the application level at the routing node to process the message~~
method further comprises:

determining from the message if the sending node does not have routing policy instructions derived from the body of the message after the message is passed to the application level of the routing node; and

generating the routing policy and returning the routing policy to the sending node if it is determined that the sending node does not have routing policy instructions derived from the message.

28. (Currently Amended) The computer program storage medium of claim 25 wherein the ~~computer process~~ method further comprises generating the routing policy at an application level in the routing node and
applying an encryption policy to the message before forwarding the message to the final destination node.

29. – 30. (Canceled)

31. (Currently Amended)

A computer program storage medium storing a computer program for executing on a computer system a ~~computer process, the computer process~~ method, the method comprising:

identifying at least one routing policy for a message, the message comprising a header and a body, wherein the header comprises information for routing the message, wherein the routing policy comprises instructions for redirecting messages based at least in part on content of the body of the message;

changing an address in the message to bypass at least one node in an overlay network based on the at least one routing policy;

identifying a final destination address to which to route the message;

incorporating the routing policy into the body of the message and issuing the message in the overlay network directly to ~~[[a]]~~ the final destination node; and

sending the at least one routing policy to a sending node in the overlay network.

32. (Canceled)

33. (Currently Amended) The computer program storage medium of claim 31 wherein the ~~computer process further comprises~~ method further comprises:

determining from the message if the sending node does not have routing policy instructions derived from the body of the message after identifying at least one routing policy; and

returning the routing policy to the sending node if it is determined that the sending node does not have routing policy instructions derived from the body of the message;

iteratively applying a plurality of routing policies to the message, each of the plurality of routing policies changing the address in the message.

34. (Canceled)

35. (Currently Amended) The computer program storage medium of claim 31 wherein the ~~computer process~~ method further comprises sending a plurality of routing policies to a sending node from a plurality of routing nodes in the overlay network, and applying an encryption policy to the message before sending the at least one routing policy to a sending node in the overlay network.

36. (Currently Amended) The computer program storage medium of claim 31 wherein the ~~computer-process~~ method further ~~comprises~~ comprises:

identifying at least one routing policy based at least in part on the address in the header of the message; and
applying a compression policy to the message.

37. (Currently Amended) The computer program storage medium of claim 31 wherein the ~~computer-process~~ method further comprises applying a transport policy to the message after changing the address in the header of the message.

38. (Currently Amended) The computer program storage medium of claim 31 wherein the ~~computer-process~~ method further ~~comprises~~ comprises:

applying a transport policy to the message only after applying each identified routing policy to the message; and
applying a security policy to the message.